

Valvola ad angolo a scarico convogliato

Angle valve with canalized discharge

Winkelventil mit kanalisiertem Abfluss

Soupape ad angle à décharge canalisé

Válvula limitadora de presión con descarga conducida

 art. **44AP**

AISI 304 - 316

ART.	DN	A	B	C	D	E	PORTATA RANGE	TARATURA in bar SETTING in bar
44AP1	40	40DIN	40DIN	40	175	60	20 m ³ /h	+0.04
44AP2	50	50DIN	50DIN	50	175	60	30 m ³ /h	+0.04
44AP3	80	80DIN	80DIN	80	290	110	50 m ³ /h	+0.04
44AP4	100	100DIN	100DIN	100	320	125	80 m ³ /h	+0.04

SPECIFICHE TECNICHE:

- Corpo e testa in AISI 304 - 316
- Tenuta in silicone
- Pressione di apertura: 0.04 bar
- Scarto di chiusura: ≤ 20%
- Temperatura di esercizio: -20°C / +120°C
- Connesioni: DIN/SMS/Clamp

TECHNICAL SPECIFICATIONS:

- Body and head in AISI 304 - 316
- Silicon Seal
- Opening pressure: 0.04 bar
- Closure gap: ≤ 20%
- Working temperature: -20°C / +120°C
- Connections: DIN/SMS/Clamp



FEATURES

